


PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference A3-257PCT International application No. PCT/US2004/002622				FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)				
				International filing date (day/month/year) 29.01.2004			Priority date (day/month/year) 29.01.2003	
Interna H01R		Patent	Classification (IPC) or bo	oth national classification	and IPC			
Applica MOLE		ICORI	PORATED					
1. 7	This ir Author	nternat rity an	ional preliminary exar d is transmitted to the	nination report has bee applicant according to	en prepa Article 3	red by this Inte 36.	ernational Preliminary Examining	
2. 7	This F	REPOF	RT consists of a total of	of 4 sheets, including t	his cove	r sheet.		
Σ	This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).							
٦	These	anne	xes consist of a total of	of 2 sheets.				
3. 1	_	_	ontains indications re	lating to the following i	tems:			
-			Priority	oninion with regard to	novelty i	nventive sten	and industrial applicability	
-			ack of unity of inventi		lovelty, i	inventive stop c	and modernal applicability	
\		⊠ F	Reasoned statement u		rith regai	rd to novelty, in	ventive step or industrial applicability;	
\	VI [Certain documents cite	ed				
1	VII [Certain defects in the i	nternational application	n			
\	VIII [Certain observations o	n the international app	lication			
Date of	f subm	nission (of the demand		Date o	f completion of the	nis report	
20.08.2004			21.09.2004					
			ddress of the internation ng authority:	al	Author	ized Officer	Josephan Pelanzeau.	
	<u></u>	Europ NI -22	ean Patent Office - P.B. 280 HV Rijswijk - Pavs B	as	Corra	iles, D		
	الا	Tel. +	31 70 340 - 2040 Tx: 31 -31 70 340 - 3016	651 epo nl		one No. +31 70	340-2645	



INTERNATIONAL PRELIMINARY EXAMINATION REPORT

JC20 Rec'd PCT/PTO 07 JUN 2005

International application No.

PCT/US2004/002622

		_			
n -	-:-		46-	report	
на	212	O1	THE	renon	

1. With regard to the **elements** of the international application (Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17)):

	Des	cription, Pages	
	1-6		as originally filed
	Cla	ims, Numbers	
	2-8,	10-15	as originally filed
	1, 9		received on 20.08.2004 with letter of 20.08.2004
	Dra	wings, Sheets	
	1/10	0-10/10	as originally filed
2.	With lang	n regard to the langu guage in which the int	age, all the elements marked above were available or furnished to this Authority in the ernational application was filed, unless otherwise indicated under this item.
	The	se elements were av	ailable or furnished to this Authority in the following language: , which is:
		the language of a tra	anslation furnished for the purposes of the international search (under Rule 23.1(b)).
		the language of publ	lication of the international application (under Rule 48.3(b)).
		the language of a tra Rule 55.2 and/or 55.	anslation furnished for the purposes of international preliminary examination (under 3).
3.	Witl inte	n regard to any nucle rnational preliminary	eotide and/or amino acid sequence disclosed in the international application, the examination was carried out on the basis of the sequence listing:
		contained in the inte	rnational application in written form.
		filed together with th	e international application in computer readable form.
		furnished subsequer	ntly to this Authority in written form.
		furnished subsequer	ntly to this Authority in computer readable form.
		The statement that to in the international a	he subsequently furnished written sequence listing does not go beyond the disclosure pplication as filed has been furnished.
		The statement that t listing has been furn	he information recorded in computer readable form is identical to the written sequence ished.
4.	The	amendments have r	esulted in the cancellation of:
		the description,	pages:
		the claims,	Nos.:
		the drawings,	sheets:

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/US2004/002622

5. 🗆	This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)).
	(Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this

6. Additional observations, if necessary:

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N) Yes: Claims 1-15

No: Claims

Inventive step (IS) Yes: Claims 1-15

No: Claims

Industrial applicability (IA) Yes: Claims 1-15

No: Claims

2. Citations and explanations

see separate sheet

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY (SEPARATE SHEET)

International application No.

PCT/US2004/002622

Re Item V

Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Reference is made to the following document:

D1: US-A-5 861 663 (SWAIN MILES FRANK ET AL) 19 January 1999 (1999-01-19)

The document D1 is regarded as being the closest prior art to the subject-matter of claim 1 and 9, and discloses:

An electrical connector for connecting between an electronic component and a circuit board via a plurality of solder balls soldering onto the circuit board, comprising an insulative housing forming a mounting surface adjacent to the circuit board and a receiving surface for supporting the electronic component, the insulative housing defining a plurality of channels extending through the mounting surface and the receiving surface; and a plurality of conductive plated surfaces respectively received in the corresponding channels, the channels having a mounting portion defining a pyramidal space to locate the solder ball.

The subject-matter of claims 1 and 9 therefore differs from this known connector in that: Instead of having a plated surface they have stamped terminals. This difference provides an improved terminal for locating and connecting the solder ball.

In the prior art the channels in the housing have a pyramidal space in the connecting end and are plated, providing a locating portion for the solder ball, although quite close the processes associated with the two methods are different. The terminal of claim 1 and the connector using such terminals of claim 9 are not obviously deduced from D1 and therefor the subject-matter of claims 1 and 9 is new and involves an inventive step. (Art. 33(2) and (3) PCT)

- 2. Claims 2-8 and 10-15 are further modifications of the subject-matter of claims 1 and 9 and therefor fulfill the requirements of Art. 33(2) and (3) PCT.
- 3. The application relates to electrical terminal and connector which has obviously an industrial applicability (Art. 33(4) PCT).



5





JC20 Rec'd PCT/PTO 07 JUN 2005

CLAIMS:

What is claimed is:

- 1. A stamped and formed conductive terminal capable of being received within a terminal channel defined in an insulative housing and between an electronic component and a circuit board, having a contact portion electrically connecting with the electronic component and a mounting portion electrically connecting with the circuit board via a solder ball, comprising:
- a first wall, a second wall connecting with the first wall in a certain angle and a third wall connecting with the second wall in a certain angle and opposite to the first wall, and the mounting portion defining a pyramidal space extending out of the insulative housing for receiving the solder ball.
- 2. The conductive terminal of claim 1 in which the mounting portion defines the pyramidal space by using a side wall connecting with an end of the first wall which circles around a fictitious central line as an axis.
- 3. The conductive terminal of claim 1 in which the mounting portion comprises a first side arm connecting with an end of the first wall and a second side arm connecting with an end of the third wall, the first side arm and the second side arm separately extend out of the insulative housing and define the pyramidal space.
- 4. The conductive terminal of claim 3 in which the mounting portion of the conductive terminal comprises a horizontal portion connecting with the second wall, the horizontal portion is between the first side arm and the second side arm, and has a certain degrees therebetween.
- 5. The conductive terminal of claim 1 in which the contact portion comprises a first spring arm formed on the first wall and a second spring arm corresponding to the first spring arm and formed on the second wall, the first spring arm and the second spring arm are adjacent to form a spring receiving structure.
- 6. The conductive terminal of claim 1 in which the pyramidal space is open at a top portion.





5

10

5



- 7. The conductive terminal of claim 1 in which a horizontal portion extends from one of the walls, the horizontal portion being located between the first and third walls.
- 8. The conductive terminal of claim 3 in which at least one of the side arms includes a recess.
- 9. An electrical connector for connecting between an electronic component and a circuit board via a plurality of solder balls soldering onto the circuit bard, having an insulative housing forming a mounting surface adjacent to the circuit board and a receiving surface for supporting the electronic component, the insulative housing defining a plurality of terminal channels extending through the mounting surface and the receiving surface, a plurality of stamped and formed conductive terminals respectively received in the corresponding terminal channels, comprising:

the conductive terminal having a first wall, a second wall connecting with the first wall in a certain angle and a third wall connecting with the second wall in a certain angle and opposite to the first wall, the conductive terminal forming a contact portion electrically connecting with the electronic component and a mounting portion electrically connecting with the circuit board via the solder ball, the mounting portion defining a pyramidal space extending out of the mounting surface of the insulative housing for receiving the solder ball.

- 10. The electrical connector of claim 9 in which the mounting portion of the conductive terminal defines the pyramidal space by using a side wall connecting with an end of the first wall which circles around a fictitious central line as an axis.
- 11. The electrical connector of claim 9 in which the mounting portion of the conductive terminal comprises a first side arm connecting with the first wall and adjacent to one end of the mounting surface and a second side arm connecting with the third wall and adjacent to one end of the mounting surface, and the first side arm and the second side arm aslant extend out of the mounting surface and are apart from each other to define a coneshaped pyramidal space.



